



Full tailored collar with neck band



Coal Harbour® Snag Resistant Contrast Stitch Sport Shirt - S4006

Product Features:

- 6.3-oz, 100% polyester flat tricot micropique knit
- Self fabric collar
- Contrast stitching at side, side slits, shoulder and button holes
- 4-button stitch detailed placket
- Coal Harbour® engraved, dyed-to-match pearlized buttons
- Reinforced topstitching throughout

Adult sizes XS-4XL

Comparable Styles:

- L4006 – Snag Resistant Contrast Stitch Ladies’ Sport Shirt
- S445 – Snag Resistant Sport Shirt
- L445 – Snag Resistant Ladies’ Sport Shirt
- Y445 – Snag Resistant Youth Sport Shirt
- TS445 – Snag Resistant Tall Sport Shirt
- S445LS – Snag Resistant Long Sleeve Sport Shirt
- S4001 – Snag Resistant Colour Block Sport Shirt
- L4001 – Snag Resistant Colour Block Ladies’ Sport Shirt

Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference

Black/
Iron Grey



Black 6C/
A Little Darker
Than 7540C

Iron Grey/
Black



A Little Darker
Than 7540C/
Black 6C

White/
Iron Grey




N/A/ A Little
Darker Than
7540C

Blue Lake/
Iron Grey



Between 645C &
646C/ A Little
Darker Than
7540C

Fabric Features / Details:



Due to the nature of 100% polyester performance fabrics, special care must be taken throughout the screen printing process

S4006 - Coal Harbour® Snag Resist Contrast Stitch Sport Shirt

GARMENT MEASUREMENTS								
Size	XS	S	M	L	XL	2XL	3XL	4XL
Chest - Half Measure	18 3/4"	20 1/4"	21 3/4"	23 1/4"	24 3/4"	26 1/4"	28 1/4"	30 1/4"
Chest - Full Measure	37 1/2"	40 1/2"	43 1/2"	46 1/2"	49 1/2"	52 1/2"	56 1/2"	60 1/2"
Body Length from HPS	28"	29"	30"	31"	32"	33"	33 1/2"	34"
Sleeve Length from CB	17 3/4"	18 1/2"	19 1/4"	20"	20 3/4"	21 1/2"	22 1/4"	23"

Finished measurements in inches. Refer to "How to Measure" guide for detailed information on measurement instructions.

ADULT General Sizing Guide								
Size	XS	S	M	L	XL	2XL	3XL	4XL
Chest	30"-32"	34"-36"	38"-40"	42"-44"	46"-48"	50"-52"	54"-55"	56"-57"
Waist	26"-29"	29"-32"	32"-35"	35"-38"	38"-41"	41"-44"	44"-47"	47"-50"
Sleeve Length-CB	31"-32"	32"-33 1/2"	34"-35"	35"-36"	36"-37"	37"-38"	38"-39"	38 1/2"-39"

COAL HARBOUR®

PRINTING INSTRUCTIONS FOR POLYESTER WICKING FABRICS

Due to the nature of 100% polyester performance fabrics, special care must be taken throughout the printing process. Here are some tips to effectively decorate our performance products.

- Garment temperature must not exceed 320°F or 160°C. Exceeding this temperature will cause the fabric to shrink, become wavy or cause dye migration.
- Dryer temperature and belt speeds must be changed accordingly for polyester fabric.
- If flashing these garments, do not exceed 1-2 seconds. Anything longer may damage the fabric as stated above.
- **Screen Printing:** These garments require the use of poly inks that cure at a lower temperature. A Dyno Grey base blocker on all colours and a second white base blocker on all dark colours are recommended. Please consult your ink supplier for more information.
- Polyester requires a longer cooling time than cotton. Avoid overlap of garments and screen-print/heat transfer until the garments are cooled. Failure to cool the fabric prior to stacking into a printer's fold may cause the fabric and applied ink to stick together.
- **Heat Transfers:** Poly mark heat transfers need to be created with an anti-migration layer in the design. This process can only be done on white or very light coloured fabric. Inks used in printing paper design need to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- **Sublimation Printing:** As noted for the poly mark heat transfers, this process can only be done on white or very light coloured fabric. Inks used in printing paper design need to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- If you heat press these garments, you must adjust the time, temperature and pressure. Failure to do so may damage the fabric as stated above.
- A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.