

2" waistband with elastic and drawstring







Tonal "ATC" logo embroidery
on bottom back of left leg

Boot cut leg with double-needle hem

Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference

Black	Sport Heather Grey	True Navy	Charcoal Heather
			
6C	N/A	539C	Multiple shades of 425C

THE AUTHENTIC T-SHIRT COMPANY® Ladies' PTech Fleece Pant - L223

Product Features:

- 12-oz, 100% polyester
- 2-inch waistband with elastic and drawstring
- Curved back yoke seam
- Boot cut leg with double-needle hem
- Reinforced topstitching throughout
- Tonal "ATC" logo embroidery on bottom back of left leg
- Tonal tipped drawcord at outside waistband
- 2" fixed elastic waistband with mid-rise fit
- "ATC" locker loop waist label
- Semi-fitted feminine pant intended for active mobility

Ladies' sizes XS-4XL

Corresponding styles:

- PTech Hooded Pullover (Adult/Youth) - F220/Y220
- PTech Hooded Jacket (Adult/Ladies'/Girls')
F221/L221/G221
- PTech Track Jacket - F222
- PTech Pant (Adult/Youth) - F223/Y224

Fabric Detail:



Smart Uses:

Step into a world of comfort with the ladies' open bottom, double-knit PTech fleece pant.

- Fitness gyms/clubs
- Gift giving
- Sports teams & events
- Coaches/athletes
- Donations/door prizes
- And much more!

GARMENT MEASUREMENTS

Finished Measurements in Inches

Size	XS	S	M	L	XL	2XL	3XL	4XL
Waist Relaxed	13	14	15	16	17 1/2	19	20 1/2	22
Inseam	30 1/4	30 3/4	31 1/4	31 3/4	32 1/4	32 1/4	32 3/4	32 3/4



PRINTING INSTRUCTIONS FOR POLYESTER WICKING FABRICS

Due to the nature of 100% polyester performance fabrics, special care must be taken throughout the printing process. Here are some tips to effectively decorate our performance products.

- Garment temperature must not exceed 320°F or 160°C. Exceeding this temperature will cause the fabric to shrink, become wavy or cause dye migration.
- Dryer temperature and belt speeds must be changed accordingly for polyester fabric.
- If flashing these garments, do not exceed 1-2 seconds. Anything longer may damage the fabric as stated above.
- **Screen Printing:** These garments require the use of poly inks that cures at a lower temperature. A Dyno Grey base blocker on all colours and a second white base blocker on all dark colours are recommended. Please consult your ink supplier for more information.
- Polyester requires a longer cooling time than cotton. Avoid overlap of garments and screen-print/heat transfer until the garments are cooled. Failure to cool the fabric prior to stacking into a printer's fold may cause the fabric and applied ink to stick together.
- **Heat Transfers:** Poly mark heat transfers need to be created with an anti-migration layer in the design. This process can only be done on white or very light colour shirts. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- **Sublimation Printing:** As noted for the poly mark heat transfers, this process can only be done on white or very light colour shirts. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- If you heat press these garments, you must adjust the time, temperature and pressure. Failure to do so may damage the fabric as stated above.
- A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.