

THE AUTHENTIC T-SHIRT COMPANY^{MD} Manteau à capuchon en molleton PTech^{MC} - F221

Caractéristiques du produit

- 12 oz, molleton à mailles doubles 100 % polyester
- Rabat coupe-vent
- Capuchon « scuba » à cordon et bouton en bâtonnet ajustables
- Manches montées
- Poches avant à fermeture à glissière
- Courbe capot avec deux panneau
- Fermeture éclair YKK du même ton avec tirette ATC^{MC}
- Longueur fermeture éclair de la bobine
- Poignets en tricot côtelé 1 x 1
- Coutures surpiquées sur l'ensemble du vêtement

Tailles adulte TP-4TG

Détail du tissu:



Couleurs disponibles et Couleurs PMS

Les couleurs des tissus sont sujets à des variations selon les lots et ne correspondront pas exactement aux couleurs de référence pantone

Noir



Noir 6C

Gris Charbon
Chiné



Teintes de
425C

Gris Sport
Chiné



N/A

Marine
Franc



539C

Vue la nature des polyester, des précautions particulières doivent être prises tout au long du procédé de décoration

F221 - ATC™ PTech™ Fleece Hooded Jacket

GARMENT MEASUREMENTS

Size	XS	S	M	L	XL	2XL	3XL	4XL
Chest - <i>Half Measure</i>	20 1/2"	22"	23 1/2"	25"	26 1/2"	28"	30"	32"
Chest - <i>Full Measure</i>	41"	44"	47"	50"	53"	56"	60"	64"
Body Length from HPS	28"	28 1/2"	29"	29 1/2"	30 1/2"	31 1/2"	32"	32 1/2"
Sleeve Length-CB	35"	35 3/4"	36 1/2"	37 1/4"	38"	38 3/4"	39 1/4"	39 3/4"

Finished measurements in inches. Refer to "How to Measure" guide for detailed information on measurement instructions.

ADULT General Sizing Guide

Size	XS	S	M	L	XL	2XL	3XL	4XL
Chest	30"-32"	34"-36"	38"-40"	42"-44"	46"-48"	50"-52"	54"-55"	56"-57"
Waist	26"-29"	29"-32"	32"-35"	35"-38"	38"-41"	41"-44"	44"-47"	47"-50"
Sleeve Length-CB	31"-32"	32"-33 1/2"	34"-35"	35"-36"	36"-37"	37"-38"	38"-39"	38 1/2"-39"



DECORATING INSTRUCTIONS FOR POLYESTER FABRICS

Due to the nature of polyester, special care must be taken throughout the decoration process. Here are some tips to effectively decorate our performance products.

- Garment temperature must not exceed 320°F or 160°C. Exceeding this temperature will cause the fabric to shrink, become wavy or cause dye migration.
- Dryer temperature and belt speeds must be changed accordingly for polyester fabric.
- If flashing these garments, do not exceed 1-2 seconds. Anything longer may damage the fabric as stated above.
- **Screen Printing:** These garments require the use of poly inks that cures at a lower temperature. A Dyno Grey base blocker on all colours and a second white base blocker on all dark colours are recommended. Please consult your ink supplier for more information.
- Polyester requires a longer cooling time than cotton. Avoid overlap of garments and screen-print/heat transfer until the garments are cooled. Failure to cool the fabric prior to stacking into a printer's fold may cause the fabric and applied ink to stick together.
- **Heat Transfers:** Poly mark heat transfers need to be created with an anti-migration layer in the design. This process can only be done on white or very light colour shirts. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- **Sublimation Printing:** As noted for the poly mark heat transfers, this process can only be done on white or very light colour shirts. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.
- If you heat press these garments, you must adjust the time, temperature and pressure. Failure to do so may damage the fabric as stated above.
- A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.